

MATERIAL SAFETY DATA SHEET

OSHA - Meets 29 CFR 1910.1200 Standards

Gator

CHEMICAL CO.

HMIS HAZARD RATINGS

| | | | |
|--------------|---|-------------------|-------------|
| HEALTH | 1 | 0 = INSIGNIFICANT | 3 = HIGH |
| FLAMMABILITY | 0 | 1 = SLIGHT | 4 = EXTREME |
| REACTIVITY | 0 | 2 = MODERATE | |

TRANSPORTATION INFORMATION

| | | | |
|-------------------------|---|--------|----------------------------|
| PROPER SHIPPING NAME: | Compounds, cleaning liquid (monoethanolamine) | | |
| HAZARD CLASS / PKG GRP: | 8 / III | REF: | 49 CFR 173.154, .203, .241 |
| IDENTIFICATION NUMBER: | NA 1760 | LABEL: | CORROSIVE |

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)

Page 1 of 2

IMPACT

| | |
|---|--|
| MANUFACTURER'S NAME Gator Chemical ADDRESS (NUMBER, STREET, P.O. BOX) P.O. Box 1990 (CITY, STATE AND ZIP CODE) Largo, FL 33779 | EMERGENCY TELEPHONE NUMBER CHEM • TEL (800) 255-3924 Outside USA (813) 248-0585 TELEPHONE NUMBER FOR INFORMATION (727) 584-5174 DATE PREPARED: January 18, 2003 SUPERSEDES: New |
|---|--|

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

| HAZARDOUS COMPONENTS <small>(SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))</small> | CAS # | % <small>(OPTIONAL)</small> | OSHA PEL | | ACGIH TWA | | SARA | RQ |
|---|------------|--------------------------------|-----------------|-------------------|-----------|-------------------|-----------|------|
| | | | PPM | MG/M ³ | PPM | MG/M ³ | TITLE III | LBS |
| Dipropylene glycol n - butyl ether | 29911-28-2 | 15 - 40 | not established | | | | | |
| Monoethanolamine | 141-43-5 | 10 - 30 | not established | | | | | |
| Potassium hydroxide (a,b) | 1310-58-3 | 1 - 5 | 2 C | | 2 C | | | 1000 |

(a) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture > 24000 lbs) or greater amounts, according to 40 CFR 302.

(b) A "C" in the OSHA PEL or ACGIH TWA column indicates ceiling limits, the concentration that should not be exceeded during any part of the working exposure.

SECTION 3 - HEALTH HAZARD DATA

| ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE | EMERGENCY AND FIRST AID PROCEDURES |
|--|---|
| INHALATION: Corrosive and irritating to upper respiratory tract and mucous membranes; may cause headache, dizziness, nausea, vomiting and malaise. | Remove affected person to fresh air; wash mouth and nasal passages with water repeatedly; if breathing difficulties persist seek medical attention. |
| SKIN: Corrosive and irritating; chemical burns may result from contact; severe irritant; prolonged contact may cause moderate reddening, swelling and possible necrosis. | Wash contacted area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention. |
| EYES: CORROSIVE; Contact with eyes is painful and irritating and will cause chemical burns, associated with redness and swelling of the conjunctiva. | Remove contact lenses. Immediately flush eyes for 15 minutes in clear running water while holding eyelids open; seek medical attention immediately. |
| INGESTION: Corrosive and irritating to digestive tract; may cause gastric distress, stomach pains and vomiting; moderately toxic, may result in red blood cell hemolysis. | Drink large quantities of water or milk; give diluted vinegar or lemon juice to conscious person; DO NOT induce vomiting; seek medical attention immediately. |

| | | | | | | |
|-----------------|------|----|------------------|----|-----------------|----|
| CARCINOGENICITY | NTP? | No | IARC MONOGRAPHS? | No | OSHA REGULATED? | No |
|-----------------|------|----|------------------|----|-----------------|----|

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)
IMPACT

Page 2 of 2
Date: January 18, 2003

SECTION 4 - FIRE FIGHTING MEASURES

| | | | |
|--|---------------------|---|---------------------|
| FLASH POINT (METHOD USED) Non-flammable | NFPA RATING None | FLAMMABLE LIMITS LEL: Not applicable | UEL: Not applicable |
|--|---------------------|---|---------------------|

EXTINGUISHING MEDIA
Carbon dioxide, water, water fog, dry chemical, chemical foam

SPECIAL FIRE FIGHTING PROCEDURES
Keep containers cool with water spray to prevent container rupture due to steam buildup; CAUTION - material is corrosive.

UNUSUAL FIRE AND EXPLOSION HAZARDS
None

SECTION 5 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: CAUTION - CORROSIVE. Wash small spills to sanitary sewer. Large spills - confine spill, soak up with approved absorbent, shovel product into approved container for disposal. For spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to CERCLA 40 CFR 302 for detailed instructions concerning reporting requirements.

SECTION 6 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Separate from oxidizing materials, metallic powders and other easily oxidized organic materials and reducing agents. CAUTION - material is corrosive. Keep this and other chemicals out of reach of children.

SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): None required while threshold limits (Section 2) are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

| | |
|---|--|
| VENTILATION LOCAL EXHAUST: Required MECHANICAL (GENERAL): Yes | SPECIAL: To maintain minimum TWA and STEL levels. OTHER: Engineering and work controls as required. |
| PROTECTIVE GLOVES: Neoprene or rubber gloves with cuffs. | EYE PROTECTION: Protective eyeglasses or chemical safety goggles. |

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls, apron, or other equipment should be worn to minimize skin contact.

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES

| | |
|--|---------------------------------------|
| BOILING POINT 212° F | SPECIFIC GRAVITY (WATER = 1) 1.040 |
| VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C | pH 13.2 |
| VAPOR DENSITY (AIR = 1) > 1 | EVAPORATION RATE (WATER = 1) < 1 |
| SOLUBILITY IN WATER Complete | % VOLATILE (BY WEIGHT) 77% |
| APPEARANCE AND ODOR Red liquid, characteristic odor | |

SECTION 9 - STABILITY AND REACTIVITY

| | |
|---------------------------------------|---|
| STABILITY UNSTABLE: STABLE: XXX | CONDITIONS TO AVOID: Extreme temperatures |
|---------------------------------------|---|

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids, strong alkalis

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

| | |
|---|------------------------------|
| HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX | CONDITIONS TO AVOID: None |
|---|------------------------------|

SECTION 10 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations for corrosive materials. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.