

MATERIAL SAFETY DATA SHEET

OSHA - Meets 29 CFR 1910.1200 Standards

Gator

CHEMICAL CO.

HMIS HAZARD RATINGS

HEALTH	1	0 = INSIGNIFICANT	3 = HIGH
FLAMMABILITY	0	1 = SLIGHT	4 = EXTREME
REACTIVITY	0	2 = MODERATE	

TRANSPORTATION INFORMATION

PROPER SHIPPING NAME:	Not Regulated		
HAZARD CLASS / PKG GRP:	Not regulated	REF:	Not Applicable
IDENTIFICATION NUMBER:	None	LABEL:	None Required

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)

Page 1 of 2

POWER PRO

MANUFACTURER'S NAME

Gator Chemical

EMERGENCY TELEPHONE NUMBER

CHEM • TEL (800) 255-3924 Outside USA (813) 248-0585

ADDRESS (NUMBER, STREET, P.O. BOX)

P.O. Box 1990

TELEPHONE NUMBER FOR INFORMATION

(727) 584-5174

(CITY, STATE AND ZIP CODE)

Largo, FL 33779

DATE PREPARED: April 20, 2003

SUPERSEDES: New

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS

(SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))

CAS #

%
(OPTIONAL)

OSHA PEL
PPM MG/M³

ACGIH TWA
PPM MG/M³

SARA
TITLE III

RQ
LBS

1-Phenoxy-2-propanol

770-35-4

1 - 5

not established

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.

Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.

SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate reddening, swelling and possible necrosis.

Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

EYES: Contact causes severe irritation and pain associated with redness and swelling of the conjunctiva.

Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

INGESTION: Moderately toxic; may cause headache, dizziness, diarrhea and general weakness; large doses may result in red blood cell hemolysis.

Give two glasses of water for dilution; Do not induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

CARCINOGENICITY

NTP?

No

IARC MONOGRAPHS?

No

OSHA REGULATED?

No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)
POWER PRO

Page 2 of 2
Date: April 20, 2003

SECTION 4 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED) Non-flammable	NFPA RATING None	FLAMMABLE LIMITS LEL: Not applicable UEL: Not applicable
--	---------------------	---

EXTINGUISHING MEDIA
Carbon dioxide, water, water fog, dry chemical, chemical foam

SPECIAL FIRE FIGHTING PROCEDURES
Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released. Material is alkaline and will irritate the eyes if product is allowed to directly contact the eyes.

UNUSUAL FIRE AND EXPLOSION HAZARDS
None

SECTION 5 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Material is alkaline and will irritate the eyes if product is allowed to directly contact the eyes. Wash small spills to sanitary sewer. Large spills - confine spill, soak up with approved absorbent, shovel product into approved container for disposal.

SECTION 6 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Keep this and other chemicals out of reach of children.

SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): None required while threshold limits (Section 2) are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

VENTILATION LOCAL EXHAUST: Required MECHANICAL (GENERAL): Yes	SPECIAL: To maintain minimum TWA and STEL levels. OTHER: Engineering and work controls as required.
PROTECTIVE GLOVES: Neoprene or rubber gloves with cuffs.	EYE PROTECTION: Protective eyeglasses or chemical safety goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls, apron, or other equipment should be worn to minimize skin contact.

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT 212° F	SPECIFIC GRAVITY (WATER = 1) 1.010
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C	pH 12.3
VAPOR DENSITY (AIR = 1) > 1	EVAPORATION RATE (WATER = 1) < 1
SOLUBILITY IN WATER Complete	% VOLATILE (BY WEIGHT) 97.8%
APPEARANCE AND ODOR Blue liquid, ether odor	

SECTION 9 - STABILITY AND REACTIVITY

STABILITY UNSTABLE: STABLE: XXX	CONDITIONS TO AVOID: Extreme temperatures
---------------------------------------	---

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX	CONDITIONS TO AVOID: None
---	------------------------------

SECTION 10 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations for alkaline materials. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.