

FIRST COAT

FLOOR SEALER

FIRST COAT is for both resilient and non-resilient floors. Its unique stain-resistant properties protect floors from asphalt and anti-oxidants (found in floor mat backings) which can permanently discolor the underlying flooring. U.L. approved.

DIRECTIONS FOR USE

PREPARATION: Remove all dirt and old finish by using a floor machine and **MOP & STRIP, QUICK STRIP, or IMPACT**. Rinse floor thoroughly and allow to dry.

APPLICATION: Apply **FIRST COAT** in thin to medium uniform coats with a finish mop. Let dry thoroughly (30 minutes) before applying next coat. Continue to add coats of **FIRST COAT** until desired base is obtained. (Maximum of 3 coats is recommended).

TECHNICAL DATA

Color.....	White Emulsion
Scent.....	Acrylic
Foaming.....	N/A
Solubility in Water.....	Complete
Density (lb/gal).....	8.65
Flash Point.....	None
pH.....	8.5

TECHNICAL DATA SHEET

Gator CHEMICAL CO., P.O. Box 1990, Largo, FL 33779

FIRST COAT

FLOOR SEALER

FEATURES

BENEFITS TO CUSTOMERS

Resilient on hard surface floors

Reduce inventory, reduce costs

Protects floor from dirt, grease, stains

Holds up even if finish wears away

Protects from deterioration from repeated stripping

At proper dilution of stripper First Coat remains

UL approved

Solid assurance to end-user

Excellent leveling

New workers look like old professionals

Easy to apply

Mop on with ease